SAFTFLO
FLUID MANAGEMENT SYSTEMS

SaFTFlo® Inserts - The Lock

What Is it?

The insert locks the chemical inside the container and provides a single point of contact to release the chemical. SaFTFlo® offers an extensive range of insert sizes, two flow rates, and a wide selection of venting options. The SaFTFlo® insert attaches to a dip tube that draws the chemical from the container.

How it works...

The SaFTFlo® insert is a part of the Closed Loop System that provides ventilation for proper flow and containment of the chemical designed to achieve safe working environments. The self-venting insert alleviates positive or negative pressure issues in the container to help prevent leaks or spills.

Materials / Options

- Standard and medium flow rates
- Venting: PE Foam Liner, SC5 Gore
- Sizes: 28 mm, 38 mm, 40 mm, 53 mm, 60 mm, 63 mm, 70 mm, Bungs
- Materials: Polypropylene, Stainless Steel, Kynar, Hastelloy, Metallocene over-mold
- For color options please contact your sales representative

For superior performance results, use the SaFTFlo® Inserts in conjunction with our full line of liquid containment and dispensing products from the SaFTFlo® Fluid Management Systems.

RDIndustries

PHONE
Phone: +1 402 455 8553
Fax: +1 402 455 8242
Toll Free: +1 800 759 7090

ADDRESS
7417 North 101 Street
Omaha
Nebraska 68122
USA

E-CONTACT
www.rdindustries.com
info@rdindustries.com
sales@rdindustries.com