



Benefits

- Dual-ports allow for dispensing from one chemical bottle into two different dispensers: thereby conserving space in tight quarters
- Dual-ports allow for multiple flow and dilution rate combinations, depending on your customer's needs
- Accurate dilutions - the dual-port cap adapter is designed to only draw from one port at a time: thus, reducing the chances of improper dilutions
- Increased product performance due to accurate dilution
- Dry break valve reduces waste and ensures clean changeover of chemical

Key Features

- Standard and Medium flow rates
- Sizes: 38mm, 40mm, 53mm, 60mm, 63mm , 70mm
- Materials:
- Plug: Polypropylene, EPDM, Kynar
- Valves: Viton, metallocene, EPDM
- Proprietary key lock available
- For color options please contact your sales representative

Compatible Products

- SaFTFlo® Inserts
- SaFTFlo® Dual Straw Insert
- SaFTFlo® Wall Mount Dispenser
- SaFTFlo® Docking Station
- SaFTFlo® Fluid Monitor

What is it and how does it work?

The SaFTFlo® Dual-Port Cap Adapter is designed for dispensing one chemical into two different types of dispensers requiring different dilutions, e.g. one dilution into a trigger bottle for window applications and another into a mop bucket for floor applications.

This is an excellent solution for those using large containers to dispense chemicals from and those wanting to reduce the number of bottles or mixing stations in a work area. It is also a great time saver not having to change over containers for different applications.

Industry Used In:



Hotels



Schools

Health Spa /
Gym

Hospitals



Grocery Stores

Patent Number: 6,669,062